

คำแนะนำในการติดตั้ง

โถสุขภัณฑ์อัจฉริยะ

บันทึกหมายเลขรุ่นของคุณ:

Record your model number: _____

English, page 14

KOHLER®






1486085-X2-A

ขอขอบคุณที่เลือก Kohler

ต้องการความช่วยเหลือหรือไม่ ติดต่อศูนย์บริการลูกค้าของเรา

- จีนแผ่นดินใหญ่: +(86) 800-820-2628, +(86) 400-820-2628
- ฮองกง (จีน) มาเก๊า (จีน) ไต้หวัน (จีน): +(852) 3125-7728
- ประเทศไทย: callcenterthailand@kohler.com, +(66) 2700-9299
- บรูไน กวม อินโดนีเซีย ญี่ปุ่น มาเลเซีย มองโกเลีย ฟิลิปปินส์ สิงคโปร์ เกาหลีใต้ เวียดนาม: +(86) 21-2606-2572
- การดูแลรักษาและทำความสะอาด: kohlerasiapacific.com/careandclean

ข้อมูลสำคัญ

-  คำเตือน: ความเสี่ยงต่อการเกิดกระแสไฟฟ้าลัดวงจร ถอดปลั๊กไฟก่อนทำการซ่อมบำรุง
 -  คำเตือน: ความเสี่ยงต่อการเกิดกระแสไฟฟ้าลัดวงจร เชื่อมต่อกับวงจรเฉพาะที่ต่อสายดินอย่างเหมาะสม ซึ่งได้รับการปกป้องด้วยอุปกรณ์ตัดไฟรั่ว (RCD) เท่านั้น ใช้ไฟฟ้า 220-240 V, 50-60 Hz, 10 A ห้ามถอดหมุดสายดินหรือใช้อะแดปเตอร์สายดิน
 -  ข้อควรระวัง: ความเสี่ยงต่อการบาดเจ็บของบุคคล ผลิตภัณฑ์นี้มีน้ำหนักมาก ให้ออกโถสุขภัณฑ์โดยใช้คนสองคน โดยใช้วิธีการยกที่เหมาะสม
 -  ข้อควรระวัง: ความเสี่ยงจากก๊าซอันตราย หากโถสุขภัณฑ์ใหม่ไม่ได้รับการติดตั้งทันที ให้นำเศษผ้ามาใส่ไว้ในหน้าแปลนยึดพื้นชั่วคราว
 -  ข้อควรระวัง: ความเสี่ยงเกี่ยวกับความเสียหายต่อทรัพย์สิน ผลิตภัณฑ์นี้ไม่มีวัสดุประสงค์เพื่อการติดตั้งในสถานที่ที่อุณหภูมิลดลงต่ำกว่า 32°F (0°C) ลักษณะการออกแบบของโถสุขภัณฑ์นี้ทำให้การระบายน้ำออกจากถังน้ำทั้งหมดทำได้ยาก หากผลิตภัณฑ์เป็นน้ำแข็ง น้ำอาจทำให้อ่างเสียหายทำให้เกิดการรั่วซึมได้
- สิ่งสำคัญ! แรงดันน้ำเข้าต่ำสุดคือ 0.07 MPa (ไคนามิก) แรงดันน้ำเข้าสูงสุดคือ 0.74 MPa

สิ่งสำคัญ! ใช้ท่อจ่ายที่ให้มาพร้อมกับผลิตภัณฑ์ ห้ามนำท่อที่เคยติดตั้งแล้วมาใช้ซ้ำ

ปฏิบัติตามประมวลกฎหมายว่าด้วยระบบประปา อาคาร และไฟฟ้าในท้องถิ่นทั้งหมด

คำแนะนำในการต่อลงดิน

ผลิตภัณฑ์นี้ควรต่อสายดิน ในกรณีที่ไฟฟ้าลัดวงจร การต่อสายดินจะช่วยลดความเสี่ยงที่จะเกิดไฟฟ้าดูดได้ โดยการให้มีสายเพื่อให้กระแสไฟฟ้ารั่วลงดิน ผลิตภัณฑ์นี้มาพร้อมกับสายไฟที่มีสายดินพร้อมปลั๊กไฟที่มีสายดิน ต้องเสียบปลั๊กเข้ากับเต้ารับไฟฟ้าที่ติดตั้งสายดินและต่อสายดินอย่างเหมาะสม

 **อันตราย:** ความเสี่ยงต่อการเกิดกระแสไฟฟ้าลัดวงจร การใช้ปลั๊กต่อสายดินอย่างไม่ถูกต้องอาจทำให้เกิดความเสี่ยงที่จะเกิดไฟฟ้าดูด


หากจำเป็นต้องซ่อมแซมหรือเปลี่ยนสายไฟหรือปลั๊กไฟ อย่าต่อสายดินเข้ากับขั้วต่อปลั๊กขั้วใด ๆ สายไฟที่หุ้มฉนวนที่มีพื้นผิวด้านนอกสีเขียว ที่มีหรือไม่มีแถบสีเหลือง นั่นคือสายดิน

ตรวจสอบกับช่างไฟฟ้าหรือเจ้าหน้าที่บริการที่มีคุณสมบัติเหมาะสม หากไม่เข้าใจคำแนะนำในการต่อลงดินโดยสมบูรณ์ หรือหากมีข้อสงสัยว่าผลิตภัณฑ์มีการต่อสายดินอย่างถูกต้องหรือไม่

ผลิตภัณฑ์นี้มีสายไฟและปลั๊กที่เฉพาะเจาะจงจากโรงงาน เพื่อให้สามารถเชื่อมต่อกับวงจรจ่ายไฟฟ้าที่เหมาะสมได้ ตรวจสอบยืนยันว่าผลิตภัณฑ์ต่อกับเต้ารับที่มีการกำหนดค่าตรงกับปลั๊ก ไม่ควรใช้อะแดปเตอร์กับผลิตภัณฑ์นี้ ห้ามตัดแปลงปลั๊กที่ให้มา หากปลั๊กไม่พอดีกับเต้ารับ ให้ติดตั้งเต้ารับที่เหมาะสมโดยช่างไฟฟ้าที่มีคุณสมบัติเหมาะสม หากต้องเชื่อมต่อผลิตภัณฑ์ใหม่ เพื่อใช้กับวงจรจ่ายไฟประเภทอื่น ควรทำการเชื่อมต่อโดยช่างบริการที่มีคุณสมบัติเหมาะสม


อย่าใช้สายต่อพ่วงกับผลิตภัณฑ์

เครื่องมือและวัสดุ



3/8 นิ้ว (10 มม.) โบลท์และแหวนรองขนาด 1/4 นิ้ว (6 มม.) ช่องเสียบลึก 1/2 นิ้ว (13 มม.)
ประแจช็อกเก็ตพร้อม

1. เตรียมจุดติดตั้ง



⚠ คำเตือน: ความเสี่ยงต่อการเกิดกระแสไฟฟ้าลัดวงจร เชื่อมต่อกับวงจรเฉพาะที่ต่อสายดินอย่างเหมาะสม ซึ่งได้รับการปกป้องด้วยอุปกรณ์ตัดไฟรั่ว (RCD) เท่านั้น ใช้ไฟฟ้า 220-240 V, 50-60 Hz, 10 A ห้ามถอดหมุดสายดินหรือใช้อะแดปเตอร์สายดิน

ประกาศ: อย่าจัดตำแหน่งส้วปาวาล์วหรือเต้ารับไฟฟ้าไว้ด้านหลังโถสุขภัณฑ์โดยตรง ตำแหน่งที่แสดงในภาพด้านบนเป็นเพียงข้อเสนอแนะเท่านั้น ตรวจสอบว่าการติดตั้งทั้งหมดเป็นไปตามกฎระเบียบที่เกี่ยวข้อง

หมายเหตุ: สายจ่ายน้ำและสายส่งกำลังสามารถอยู่ด้านหลังด้านหนึ่งของโถสุขภัณฑ์

โถสุขภัณฑ์มีเซ็นเซอร์ตรวจจับความเคลื่อนไหวเพื่อเปิดฝารองนั่งโดยอัตโนมัติเมื่อตรวจพบการเคลื่อนไหว เซ็นเซอร์นี้มีระยะสูงสุด 51-1/2" (1,300 มม.) สามารถปรับตั้งความไวหรือปิดได้โดยใช้รีโมทคอนโทรล โปรดดูคู่มือสำหรับเจ้าของบ้าน

ติดตั้งตัวจ่ายน้ำ



- ติดตั้งตัวหยุดการจ่ายน้ำ
- ล้างสายจ่ายน้ำลงในถังหรือภาชนะอื่น ๆ เพื่อกำจัดเศษวัสดุ

ติดตั้งส่วนจ่ายไฟฟ้า

หมายเหตุ: สายไฟสำหรับโถสุขภัณฑ์ยาว 1.2 ม. นอกโถสุขภัณฑ์

- ติดตั้งเต้ารับแบบต่อลงดิน 220-240 V, 50/60 Hz ที่ป้องกันโดย RCD ภายในขนาดที่แสดง


2. ถอนการติดตั้งโถสุขภัณฑ์ที่มีอยู่ (ถ้ามี)



! ข้อควรระวัง: ความเสี่ยงจากก๊าซอันตราย หากโถสุขภัณฑ์ใหม่ไม่ได้รับการติดตั้งทันที ให้นำเศษผ้ามาใส่ไว้ในหน้าระบาย

- ปิดการจ่ายน้ำ
- กดชักโครกและใช้ฟองน้ำซับน้ำที่ค้างอยู่ออกจากถังพักน้ำและโถสุขภัณฑ์
- ถอดวาล์วปิดการจ่ายน้ำ (ถ้ามี) และนำถังและโถที่เหลื้อออก
- ขูดเศษขี้ผึ้งที่เหลื้ออยู่ออกจากหน้าแปลน
- ปลดสลักเกลียวตัว T ออกจากหน้าแปลน
- ถอดหน้าแปลนออกจากพื้นและทิ้งสลักเกลียวตัว T และหน้าแปลน


3. วางตำแหน่งโถสุขภัณฑ์



⚠️ ข้อควรระวัง: ความเสี่ยงต่อการบาดเจ็บของบุคคล ผลิตภัณฑ์นี้มีน้ำหนักมาก ให้ยกโถสุขภัณฑ์โดยใช้คนสองคน โดยใช้วิธีการยกที่เหมาะสม


- ระบุจุดกึ่งกลางของรูระบายและทำเครื่องหมายเส้นกึ่งกลาง “+” ที่ตั้งฉากกับผนัง
- วางโถสุขภัณฑ์ในแนวนอนบนเบาะอย่างระมัดระวัง
- ระบุจุดศูนย์กลางของท่อลงดินที่ติดอยู่บนโถสุขภัณฑ์ ทำเครื่องหมายเส้นกึ่งกลางทั้งสี่ด้านของโถสุขภัณฑ์
- ค่อย ๆ ลดระดับโถสุขภัณฑ์ลงบนพื้น ตรวจสอบว่าโถสุขภัณฑ์อยู่ในแนวเดียวกับแนวกึ่งกลางของรูระบายน้ำที่ทำเครื่องหมายบนพื้น
- ทำเครื่องหมายเส้นกึ่งกลางของตำแหน่งรูยึดแผ่นยึดทั้งด้านซ้ายและด้านขวาของโถสุขภัณฑ์

4. เจาะรูสำหรับยึด



- ทำเครื่องหมายรูยึดบนพื้นตามการวัดที่กำหนด
- เจาะรูขนาด 3/8 นิ้ว (10 มม.) ที่ตำแหน่งที่ทำเครื่องหมายไว้
- สอดขอเกี่ยวเข้าไปในรูเจาะ

5. วางตำแหน่งท่อลงพื้น





หมายเหตุ: วงแหวนซีเมนต์ถูกติดตั้งไว้ล่วงหน้าบนหน้าแปลนที่พื้นที่ที่จัดไว้

- จัดวางท่อลงพื้นให้เข้าที่เหนือระบายน้ำ
- จัดแนวรูของรางน้ำให้ตรงกับรูยึดพื้น
- หากจำเป็นต้องปรับให้ตรงกับรู ให้คลายน็อตข้องออก
- ตั้งค่าระยะห่างที่ต้องการ โดยหมุนข้อง และปรับพอร์ระบายด้านบนสำหรับข้องกลับไปตำแหน่งตั้งต้น
- ต้องล๊อคน็อตหลังจากปรับแล้ว
- นำท่อลงพื้นออกจากพื้นและวางไว้ข้าง ๆ

ติดตั้งชุดประกอบวงแหวนหน้าแปลนและซีเมนต์

- จัดแนวหน้าแปลนให้ตรงกับระบายบนพื้น
- กดหน้าแปลนและชุดวงแหวนแฉีกเพื่อยึดบนพื้น


6. ติดตั้งตัวยึดและท่อลงพื้น



หมายเหตุ: สลักและแหวนรองสามชุดที่ลูก้าต้องจัดเตรียมสำหรับการติดตั้งท่อลงพื้น

- ติดตั้งโครง L บนพื้นโดยใช้อุปกรณ์ที่ให้มา
- จัดแนวรางน้ำให้ตรงกับรูระบายน้ำ
- ยึดท่อลงพื้นบนพื้นด้วยสลักเกลียวและแหวนรอง


7. ติดตั้งโถสุขภัณฑ์



ข้อควรระวัง: ความเสี่ยงต่อการบาดเจ็บของบุคคล ผลิตภัณฑ์นี้มีน้ำหนักมาก ให้ยกโถสุขภัณฑ์โดยใช้คนสองคน โดยใช้วิธีการยกที่เหมาะสม

- เดินสายจ่ายน้ำและสายไฟออกจากด้านหลังหรือด้านข้างของโถสุขภัณฑ์เพื่อติดตั้ง
- ให้ยกโถสุขภัณฑ์ขึ้นเหนือท่อน้ำ และจัดตำแหน่งท่อทางออกให้อยู่เหนือทางเข้าของท่อน้ำ โดยมีความช่วยเหลือ
- ค่อย ๆ ลดระดับโถสุขภัณฑ์ลงบนท่อน้ำ
- ตรวจสอบว่าสายจ่ายน้ำและสายไฟไม่ถูกหนีบอยู่ใต้โถสุขภัณฑ์
- ติดตั้งฝาที่เหมาะสมที่ด้านข้างของโถสุขภัณฑ์ ใช้ฝาปิดแบบสล็อตเพื่อรองรับสายจ่ายและสายไฟที่เดินออกไปด้านข้าง ไม่เช่นนั้นให้ใช้ฝาปิดแบบแข็ง
- ต่อท่อจ่ายน้ำเข้ากับสตีปวาล์ว
- เปิดการจ่ายน้ำ


8. ยึดโถสุขภัณฑ์ให้แน่น



⚠️ ข้อควรระวัง: ความเสี่ยงเกี่ยวกับความเสียหายต่อผลิตภัณฑ์ ห้ามขันสกรูแน่นเกินไป โถสุขภัณฑ์อาจบิ่นหรือแตกได้หากขันสกรูแน่นเกินไป

- สอดปลอกยางเข้าไปในรูแต่ละรูที่ด้านข้างของ โถสุขภัณฑ์
- สอดสกรูเข้าไปในรูแต่ละรูและขันให้แน่น อย่าขันจนแน่นเกินไป
- ติดตั้งฝาครอบเหนือสกรูแต่ละตัว ควรติดตั้งฝาด้านนอกของโถสุขภัณฑ์
- เสียบปลั๊กไฟเข้ากับเต้ารับไฟฟ้า
- รอให้ไฟกลางคืนหยุดกะพริบ แสดงว่าขั้นตอนการเริ่มต้นทำงานเสร็จสมบูรณ์แล้ว
- กดปุ่มกดชักโครกและปล่อยให้โถสุขภัณฑ์เติมน้ำจนเต็ม
- ตรวจสอบการเชื่อมต่อทั้งหมดว่ามีกรรั่วไหลหรือไม่ และทำการปรับตามความจำเป็น

9. ติดตั้งแท่นชาร์จ



- จัดตำแหน่งแท่นวางไว้ที่ตำแหน่งยึดที่ต้องการ
- ยืนยันว่าแท่นวางอยู่ในแนวระดับ
- ใช้ดินสอทำเครื่องหมายตำแหน่งรูยึดทั้งสองตำแหน่ง
- สำหรับการติดตั้งเข้ากับโครงคร่าวหรือพื้นผิวไม้อื่น ๆ: เจาะรู 1/16" (2 มม.) ที่แต่ละตำแหน่งที่ทำเครื่องหมายไว้
- สำหรับการติดตั้งโดยใช้ทุกยึดผนัง: เจาะรู 1/4" (6 มม.) ที่แต่ละตำแหน่งที่ทำเครื่องหมายไว้ ใส่ทุกยึดผนังที่ให้มาลงในรู
- จัดตำแหน่งแท่นวางไว้เหนือทุกหรือเครื่องหมาย ยึดด้วยสกรูที่ให้มา
- ถอดและเก็บฝาปิดช่องใส่แบตเตอรี่
- ติดตั้งแบตเตอรี่ AA สี่ก้อนที่ให้มาให้ตรงตามแนวที่แสดง
- ติดตั้งฝาปิดช่องใส่แบตเตอรี่กลับเข้าที่
- ใส่รีโมทคอนโทรลเข้ากับแท่นวาง


การจับคู่รีโมท

หมายเหตุ: ต้องจับคู่รีโมทคอนโทรลกับฟารองนั่งก่อนใช้งาน รีโมทคอนโทรลที่ให้มาควรมีการจับคู่กับฟารองนั่งของคุณอยู่แล้ว หากจำเป็นต้องใช้รีโมทคอนโทรลที่เปลี่ยนทดแทน ให้ทำตามคำแนะนำด้านล่างเพื่อจับคู่กับฟารองนั่งของคุณ

หมายเหตุ: สามารถจับคู่รีโมทคอนโทรลกับฟารองนั่งชักโครกได้คราวละหนึ่งเครื่องเท่านั้น

- ย้ายรีโมทคอนโทรลใหม่เข้าไปใกล้ฟารองนั่ง
- กดไอคอน "เครื่องเป่าแห้ง" บนรีโมทคอนโทรลค้างไว้จนกระทั่งไอคอนกะพริบ
- กดไอคอน "ด้านหน้า" และ "ด้านหลัง" บนโดสุกกันชนฯ ค้างไว้พร้อมกันจนกว่าจะได้ยินเสียงบีบ
- เมื่อไอคอนบนรีโมทคอนโทรลหยุดกะพริบ แสดงว่าจับคู่รีโมทคอนโทรลเรียบร้อยแล้ว

10. การตรวจสอบการติดตั้ง



หมายเหตุ: คุณสมบัติการชำระ โถสุขภัณฑ์จะไม่ทำงานหากไม่มีคนนั่ง ในการทดสอบคุณสมบัติการทำความสะอาด จะต้องปิดคลุมบริเวณเซ็นเซอร์

หมายเหตุ: เมื่อทดสอบคุณสมบัติการทำความสะอาด ให้คลุมฝารองนั่งด้วยฟิล์มพลาสติกหรือใช้มือปิดก้านฉีด

- ใช้มือปิดก้านทำความสะอาดหรือท่อพลาสติกให้ทั่วที่นั่ง
- ใช้มือหรือผ้าเปียกคลุมบริเวณเซ็นเซอร์ตรวจจับการใช้น้ำที่ติดตั้งอยู่ด้านหลังหน้าขาของที่นั่ง
- ใช้รีโมทคอนโทรลเพื่อทดสอบคุณสมบัติของโถสุขภัณฑ์
- โปรดดูคู่มือสำหรับเจ้าของบ้านที่มาพร้อมกับผลิตภัณฑ์ในส่วนความช่วยเหลือในการแก้ไขปัญหาทั่วไป

Installation Instructions






Smart Toilet

Thank You for Choosing KOHLER

Need help? Contact our Customer Care Center.

- Mainland China: +(86) 800-820-2628, +(86) 400-820-2628
- Hong Kong (China), Macau (China), Taiwan (China): +(852) 3125-7728
- Thailand: callcenterthailand@kohler.com, +(66) 2700-9299
- Brunei, Guam, Indonesia, Japan, Malaysia, Mongolia, Philippines, Singapore, South Korea, Vietnam: +(86) 21-2606-2572
- **Care and cleaning:** kohlerasiapacific.com/careandclean

Important Information

-  **WARNING: Risk of electric shock.** Disconnect the power before servicing.
-  **WARNING: Risk of electric shock.** Connect only to a properly grounded dedicated circuit protected by a Residual Current Device (RCD). Use 220-240 V, 50-60 Hz, 10 A service. Do not remove the grounding pin or use a grounding adapter.
-  **CAUTION: Risk of personal injury.** This product is heavy. Lift the toilet with two people, using proper lifting technique.
-  **CAUTION: Risk of hazardous gases.** If the new toilet is not installed immediately, temporarily place a rag in the floor flange.
-  **CAUTION: Risk of property damage.** This product is not intended to be installed where temperatures will drop below 32°F (0°C). The design of the toilet makes it difficult to remove all water from the tank. If frozen, the water could damage the tank resulting in leaking.

IMPORTANT! The minimum water inlet pressure is 0.07 MPa (dynamic). The maximum water inlet pressure is 0.74 MPa.

IMPORTANT! Use the supply hose provided with the product. Do not reuse a previously installed hose.

Follow all local plumbing, building, and electrical codes.

Grounding Instructions

This product should be grounded. In the event of an electrical short circuit, grounding reduces the risk of electric shock by providing an escape wire for the electric current. This product is equipped with a cord having a grounding wire with a grounding plug. The plug must be plugged into an electrical outlet that is properly installed and grounded.

⚠ DANGER: Risk of electric shock. Improper use of the grounding plug can result in a risk of electric shock.


If repair or replacement of the cord or plug is necessary, do not connect the grounding wire to either flat blade terminal. The wire with insulation having an outer surface that is green with or without yellow stripes is the grounding wire.

Check with a qualified electrician or service personnel if the grounding instructions are not completely understood, or if in doubt whether the product is properly grounded.

This product is factory equipped with a specific electric cord and plug to permit connection to a proper electric circuit. Verify that the product is connected to an outlet having the same configuration as the plug. No adapter should be used with this product. Do not modify the plug provided. If the plug does not fit the outlet, have the proper outlet installed by a qualified electrician. If the product must be reconnected for use on a different type of electric circuit, the connection should be made by qualified service personnel.


Do not use an extension cord with the product.

Tools and Materials



3/8" (10 mm) 1/4" (6 mm) Bolts and Washers 1/2" (13 mm) Deep Socket
Socket Wrench with

1. Prepare the Site



⚠ WARNING: Risk of electric shock. Connect only to a properly grounded dedicated circuit protected by a Residual Current Device (RCD). Use 220-240 V, 50-60 Hz, 10 A service. Do not remove the grounding pin or use a grounding adapter.

NOTICE: Do not locate the supply stop or electrical outlet directly behind the toilet. The locations illustrated above are suggested. Verify that all installations adhere to applicable codes.

NOTE: The water supply line and power line can be either side of the toilet.

The toilet is equipped with a motion sensor to automatically open the cover when movement is sensed. This sensor has a maximum range of 51-1/2" (1300 mm). Sensitivity can be adjusted or turned off using the remote control. Refer to the Homeowners Guide.

Install the Water Supply



- Install the water supply stop.
- Flush the water supply line into a bucket or other container to remove debris.

Install the Electrical Service

NOTE: The toilet power cord is 1.2 m in length outside of the toilet.

- Install a dedicated 220-240 V, 50/60 Hz grounding-type receptacle, protected by an RCD, within the dimensions shown.


2. Uninstall the Existing Toilet (If Any)



⚠ CAUTION: Risk of hazardous gases. If the new toilet is not installed immediately, temporarily place a rag in the drain hole.

- Turn OFF the water supply.
- Flush the toilet, and use a sponge to remove the remaining water from the tank and bowl.
- Disconnect water supply shut-off valve (if any), and remove the residual tank and bowl.
- Scrape away any remaining wax residue from the flange.
- Uninstall T-bolts from the flange.
- Remove the flange from the floor and discard the T-bolts and flange.


3. Position the Toilet



⚠ CAUTION: Risk of personal injury. This product is heavy. Lift the toilet with two people, using proper lifting technique.


- Identify the centerpoint of the drain hole and mark the “+” centerlines perpendicular to the wall.
- Carefully place the toilet horizontally on the cushion.
- Identify the centerpoint of a trapway mounted on the toilet. Mark the centerlines on all four sides of the toilet.
- Carefully lower the toilet onto the floor. Verify that the toilet is aligned to the centerline of the drain hole marked on the floor.
- Mark the centerline of the bracket mounting hole positions on both the left and right sides of the toilet.

4. Drill the Mounting Holes



- Mark the mounting hole on the floor according to given measurements.
- Drill the 3/8" (10 mm) holes on the marked positions.
- Insert the anchor into the drilled holes.

5. Position the Trapway





NOTE: The wax ring is preinstalled on the provided floor flange.

- Set the trapway in place over the drain hole.
- Align the trapway holes with floor mounting holes.
- If adjustment is required to match the holes, loosen the elbow nut.
- Set the required distances by rotating the elbow and adjust back the elbow upper drain port to the home position.
- The nut must be locked after adjustment.
- Remove the trapway from the floor and set aside.

Install the Flange and Wax Ring Assembly

- Align the flange with the drain hole on the floor.
- Press the flange and wax ring assembly to secure on the floor.


6. Install the Bracket and Trapway



NOTE: Three sets of bolts and washers to be arranged by the customer for trapway installation.

- Install the L-brackets on the floor using the hardware provided.
- Align the trapway with the drain hole.
- Secure the trapway on the floor with the bolts and washers.


7. Install the Toilet



⚠ CAUTION: Risk of personal injury. This product is heavy. Lift the toilet with two people, using proper lifting technique.

- Route the water supply line and power cord out the back or the side of the toilet for your installation.
- With assistance, lift the toilet over the trapway and align the outlet tube over the trapway inlet.
- Carefully lower the toilet onto the trapway.
- Verify that the water supply line and electrical cord are not pinched under the toilet.
- Install the appropriate cap to the side of the toilet. Use the slotted cap to accommodate the supply line and cord routed out the side. Otherwise, use the solid cap.
- Connect the water supply hose to the supply stop.
- Turn ON the water supply.


8. Secure the Toilet



⚠ CAUTION: Risk of product damage. Do not overtighten the screws. The vitreous shell may chip or break if the screws are overtightened.

- Insert a grommet into each of the holes on the side of the toilet.
- Insert a screw into each of the holes and tighten securely. **Do not overtighten!**
- Install a cap over each screw. The caps should be flush with the exterior of the toilet.
- Plug the power cord into the electrical outlet.
- Wait for the nightlight to stop blinking, indicating that the start-up procedure is complete.
- Press the flush button and let the toilet fully refill.
- Check all connections for leaks, and make adjustments as needed.

9. Install the Docking Station



- Position the docking station at the desired mounting location.
- Confirm that the docking station is level.
- Using a pencil, mark the two mounting-hole locations.
- For installation into a stud or other wood surface:** Drill a 1/16" (2 mm) hole at each of the marked locations.
- For installation using wall anchors:** Drill a 1/4" (6 mm) hole at each of the marked locations. Install the provided wall anchors into the holes.
- Position the docking station over the anchors or marks. Secure with the provided screws.
- Remove and retain the cap to the battery compartment.
- Install the four provided AA batteries in the orientation shown.
- Reinstall the cap to the battery compartment.
- Place the remote control on the docking station.


Pairing to the Toilet

NOTE: A remote control must be paired with the toilet seat before use. The included remote control should already be paired with your seat. If a replacement remote control is required, follow the instructions below to pair with your seat.

NOTE: Only one remote control can be paired with the toilet seat at a time.

- Move the new remote control near the toilet seat.
- Press and hold the **"Dryer"** icon on the remote control until all the icons blink twice.
- Simultaneously press and hold the **"Front"** and **"Rear"** icons on the toilet control panel until a beep is heard.
- When the icons on the remote control stop blinking, the remote control has been paired.

10. Installation Checkout



NOTE: The toilet cleansing features will not function without an occupant. To test cleansing features, the occupancy sensor area must be covered.

NOTE: When testing the cleansing features, cover the seat with plastic wrap or cover the wand with your hand.

- Cover the cleansing wand with your hand or span plastic wrap across the seat.
- Use your hand or a wet cloth to apply pressure to the occupancy sensor area located on the front right side of the seat.
- Use the remote control to test the toilet features.
- Refer to the Homeowners Guide packed with the product for general troubleshooting aid.

kohlerasiapacific.com

THE BOLD LOOK
OF **KOHLER**®

©2024 Kohler Co.



1486085-X2

1486085-X2-A