



72" x 42" drop-in whirlpool bath with Bask® heated surface

K-1164-W1

Features

- Bask® heated surface creates spa-like relaxation with soothing warmth on your back, shoulders, and neck
- Three heat settings allow you to customize the surface temperature
- Single-speed whirlpool offers performance and value, with six fully adjustable jets
- Hydromassage flow and direction can be controlled at each iet
- Oval basin creates a spacious bathing experience
- Integral lumbar support and armrests offer extra comfort while bathing



Acrylic

Hydrotherapy

Whirlpool

Installation

- Reversible drain
- Drop-in or undermount

Required Products/Accessories

K-T37391 Rotary-turn bath drain trim K-T37392 Rotary-turn bath drain trim

or

K-37385 rough-in cable drain, PVC, 45" cable K-78439 45" cable bath drain

Recommended Products/Accessories

K-11677 Bath Drain

K-1491 Bath/Whirlpool Pillow

K-1601 Bath/whirlpool footstop, removable

K-577 Under-Mount Installation Kit

K-9696 Whirlpool 6-Jet Trim Kit

K-23726 Drain treatment

K-23732 Tub & shower cleaner

K-31796 Above-the-floor bath drain kit

K-31798 Bath drain kit



Codes/Standards

ASME A112.19.7/CSA B45.10 CSA B45.5/IAPMO Z124 ASTM E162 UL 1795 IAPMO Certification UL Listed


KOHLER® Plastic Baths and Shower Bases Lifetime Limited WarrantyKOHLER® Hydrotherapy Components Five-Year Limited Warranty

See website for detailed warranty information.

Available Colors/Finishes

Color tiles intended for reference only.

| Color | Code | Description |
|-------|------|-------------|
| | 0 | White |








Sunward®

72" x 42" drop-in whirlpool bath with Bask® heated surface

K-1164-W1



Required Electrical Service

One dedicated circuit required, protected with Class A Ground-Fault Circuit-Interrupter (GFCI). Outside North America, this device may be known as a Residual Current Device (RCD).

Pump, Heated 120 V, 15 A, 60 Hz

Surface:

Technical Information

All product dimensions are nominal.

Drain location: Reversible

Basin area, bottom: 55-1/4" x 23-1/2" (1403 mm x 597 mm) Basin area, top: 64-1/2" x 32" (1638 mm x 813 mm)

Weight: 118 lbs (53.5 kg)
Minimum floor load: 37 lbs/ft² (180.6 kg/m²)

Water depth: 15" (381 mm)
Water capacity: 75 gal (283.9 L)

Template: Drop-in, 1042557-7, required, included

Electrical component Pump: 120 V, 7 A, 60 Hz

rating: Heated Surface: 120 V, 0.5 A, 60 Hz, 65

W

Pump speed: Single 1-800-4KOHLER (1-800-456-4537)

Notes

Measure your actual product for rough-in details.

Install this product according to the installation instructions.

The hot water supply should be 70% of the capacity of the bath or greater. Installations will vary.

