# **KOHLER**<sub>®</sub>

Elongated toilet bowl with skirted trapway K-20148

# Features

- Elongated bowl offers added room and comfort
- Skirted trapway simplifies cleaning
- Revolution 360<sup>®</sup> flushing technology generates a forceful swirling motion to keep the bowl clean longer
- Comfort Height<sup>®</sup> feature offers chair-height seating that makes sitting down and standing up easier for most adults
- 2-1/8" (54 mm) glazed trapway
- CleanCoat<sup>™</sup> surface treatment inhibits the growth of water scale and mineral stains for improved ease of cleaning
- Combines with the K-20203/-RA or K-20204 tank to create a complete K-20197/-RA Betello<sup>™</sup> or K-20198 Betello<sup>™</sup> ContinuousClean toilet
- Patented ReadyLock<sup>®</sup> installation system, a simple solution for skirted toilets, saves time, hassle, and eliminates the need to drill into the floor for standard 12" (305 mm) rough-in

# Installation

- Standard 12" (305 mm) rough-in
- 10" and 14" (254 mm and 356 mm) rough-in kits also available
- Seat sold separately

## **Recommended Products/Accessories**

K-20203 Toilet tank, 1.28 gpf K-20203-RA Toilet tank, 1.28 gpf K-23726 Drain treatment





Codes/Standards ASME A112.19.2/CSA B45.1 EPA WaterSense® IAPMO Certification

# KOHLER<sup>®</sup> Toilets and Seats Limited Warranty

See website for detailed warranty information.

# **Available Colors/Finishes**

Color tiles intended for reference only.

Color	Code	Description
	0	White
	96	Biscuit
	NY	Dune
	95	lce™ Grey
	7	Black Black™





# Betello® Elongated toilet bowl with skirted trapway K-20148

No image available. This product is a component and not intended to be a standalone installation.

## **Technical Information**

All product dimensions are nominal.		
Toilet type:	Floor-mount	
Waste Outlet:	Floor	
Bowl shape:	Elongated	
Flush type:	Revolution 360	
Water surface size:	9-3/8" x 7-3/16" (238 mm x 183 mm)	
Rough-in:	12" (305 mm)	

#### **Fixture Supply Requirements**

Min static pressure:15 psi (103.4 kPa)Max static pressure:80 psi (551.6 kPa)

#### Notes

Install this product according to the installation instructions.

