

Round two-function handshower, 2.5 gpm K-21335

Features

- Advanced spray engine provides two spray experiences: full coverage and targeted massage
- Full coverage spray produces an encompassing spray ideal for everyday use
- Targeted spray is a focused stream for targeting sore muscles or use as a utility spray
- Intuitive and easy push-button activation to switch between two sprays
- Ergonomic design is comfortable and easy to grip
- MasterClean[™] sprayface features an easy-to-clean surface that withstands mineral buildup and maximizes spray performance
- 2.5 gpm (9.5 lpm) maximum flow rate
- Contains flow-regulating check valve for backflow prevention

Material

KOHLER[®] finishes resist corrosion and tarnishing

Installation

- Bracket or slidebar required for wall-mount installation
- Deck-mount holder required for deck-mount installation

Required Products/Accessories

K-8593 72" Shower Hose

or

K-9514 60" Shower Hose

Recommended Products/Accessories K-23723 Faucet cleaner

Optional Products/Accessories

K-9660 Vacuum Breaker





Codes/Standards

ASME A112.18.1/CSA B125.1 DOE - Energy Policy Act 1992 OBC IAPMO Certification

KOHLER[®] Faucet Lifetime Limited Warranty

See website for detailed warranty information.


Available Colors/Finishes

Color tiles intended for reference only.

Color	Code	Description
	CP	Polished Chrome
	SN	Vibrant® Polished Nickel
	AF	Vibrant® French Gold
	BN	Vibrant® Brushed Nickel
	BV	Vibrant® Brushed Bronze
	BL	Matte Black
	2MB	Vibrant® Brushed Moderne Brass
	ΤT	Vibrant Titanium

KOHLER, Faucets

Shift®+ Round two-function handshower, 2.5 gpm K-21335



Technical Information

All product dimensions are nominal.

Drain included:

Handshower:

Rated maximum 2.5 gal/min (9.5 l/min) flow:

No

Notes

For use with automatic compensating valves rated at 2.2 gal/min (8.3 l/min) or less. Install this product according to the installation instructions.

Plumbing codes may require that a vacuum breaker be installed in-line to handshowers. Please consult local plumbing codes.

OBC compliant when installed to the specific requirements of these regulations.

