

No.2 KOHLER ROAD, SANSHUI CENTRAL INDUSTRIAL PARK, LEPING TOWN, SANSHUI DIST., FOSHAN, GUANGDONG, PRC POST CODE: 528137 广东省佛山市三水区乐平镇三水中心工业园区科勒大道2号 邮编: 528137 8# MENGSHAN RD, ECONOMIC DEVELOPMENT ZONE OF HUANTAI, ZIBO, SHANDONG, CHINA POST CODE: 256410

8# MENGSHAN RD, ECONOMIC DEVELOPMENT ZONE OF HUANTAI, ZIBO, SHANDONG, CHINA POST CODE: 256410 山东省淄博市桓台经济开发区蒙山路8号 邮编: 256410 NO.1 KOHLER STREET, ECONOMIC DEVELOPMENT ZONE OF FAKU COUNTY, SHENYANG LIAONING PROVINCE, PRC POST CODE: 110400 辽宁省沈阳市法库经济开发区科勒大街1号 邮编: 110400

INSTALL NEW LAVATORY

- Cut the template on the cutout line.
 Locate the installation position. Make sure the overflow hole is on the front of the countertop and the logo is on the faucet side.
- Position the template on the countertop to ensure clearance between the lavatory, faucet, and backsplash.
- Verify cabinet clearance beneath the countertop.
- Trace the template on the countertop with a pencil.
- Re-check the clearance between the lavatory, faucet, backsplash, and cabinet. Adjust the template accordingly.
- Drill a 13mm hole on the inside of the
- cutout opening.
 Cut the opening in the countertop along the inside edge of the pencil line.
- Temporaily position the lavatory in the
- opening, and adjust to fit. CAUTION: Risk of personal injury or product damage. Large lavatories are very heavy. Get help lifting the lavatory into place.
- Trace a pencil line around the outside edge of the lavatory.
- Remove the lavatory.Install the faucet and drain according to the manufacturers instructions.
- Apply two beads of sealant to the inside of the pencil line.
- Spread the sealant evenly with a putty knife.
- Carefully position the lavatory in the cutout, and press down firmly.
- CAUTION: Risk of personal injury or product damage.Get help lifting the lavatory into place.
- Immediately wipe away any excess sealant, and fill any voids as needed.
- Verify that the lavatory has not moved out of position.Allow the sealant to cure for at least 30
- minutes before proceeding.
- Connect the faucet supply lines.
- Connect the drain assembly.Open the faucet valves, and check for
- leakage.Clean up with a non-abrasive cleaner.

NOTE:

- Please use soft and wate-proof sealant.
- Do not use epoxy resin adhesive or sealing materials that will expand after concreting, such as cement. Otherwise, kohler will not be responsible for any product damage caused by such material.

IMPORTANT CONSUMER INFORMATION (CARE AND CLEANING)

To keep your lavatory looking new, make sure you rinse it out thoroughly after each use. **DO NOT USE ABRASIVES** on this product, as they will scratch and ruin the surface. Stubborn stains, paint, or tar can be removed with turpentine or paint thinner.

Do not use the product in the water below $0^\circ \text{C}.$

CAUTION: Please do not use hard materials (like scouring pad) to clean product surface, especially the product logo.


RECOMMENDED DRAIN (NOT SUPPLED):

K-30900T-0 Click Drain













安装新脸盆

- 将切割图沿切割线切出。
 请确定产品安装位置,注意溢水孔位置 在安装台面前端,商标位置在水龙头安 装面一侧。
- 将切割图放在盥洗台上,确保脸盆、水 龙头和防溅挡板之间有足够的距离。
- 查核盥洗台下的储物柜也有足够空间。
- 用炭笔沿切割图在盥洗台面划线。
- 再次检查脸盆、水龙头、防溅水板及储 物柜的空间及距离。如有需要可调校切 割图的位置。
- 用一个13mm的钻头,在切割口内侧钻一 个导孔。
- 沿着自切割图勾划出来的铅笔线内侧切 开台面。
- 暂将脸盆放入台面开口,校正位置。
 小心:提防身体受伤或损坏产品。因 大型脸盆相当重,需找人帮您一起搬动及安放。
- 用炭笔沿脸盆外缘在盥洗台上划线。
- 然后将脸盆移开。
 按照制造商的指引,安装水龙头和排水管道。
- 沿炭笔导线内侧涂两滴封边胶。
- 用涂油灰刀将其抹匀。
- 小心地将脸盆置于台面切口适当位置, 向下按牢。

▲ 小心:提防身体受伤或损坏产品,需 找人帮您一起搬动及安放。

- 立即擦去多余的封边胶,如脸盆外缘与 台面间有缝隙,即用胶填密。
 检查脸盆的位置准确。
- 最少待三十分钟,让封边胶干透后,方
- 可继续进行安装。 • 连接水龙头供水管。
- 连接外龙头层水门
 连接排水装置。
- 开启水龙头阀门,检查有否渗漏。
- 用非腐蚀性清洁剂来清洁。
- 注意:
- 只能使用柔软的防水密封胶。
- 切勿使用环氧树脂或水泥等硬化后体积变大的密封材
 料,科勒对所有因此而引起的陶瓷破裂恕不负责。

用户须知 (护理和清洁)


为保持脸盆光洁如新,须确保每次使用后彻底冲洗干净,切 勿使用腐蚀性的清洁剂,以免刮花及破坏脸盆的表面。要清 除顽固污垢,油漆或柏油,可使用松油或油漆稀释剂。

不要在0℃以下的水环境中使用。

警告:请勿使用钢丝球等硬质材料擦洗产品表面,特别是产品商标处。

推荐落水器 (不随货供应):

K-30900T-0弹跳式落水



1443139-T01-B

© Copyright Kohler China Investment Co., Ltd. 2021 ©版权为科勒(中国)投资有限公司所有 2021